



Features

- ✓ CRI>83
- ✓ No Flicker
- ✓ UGR<19
- ✓ Beam Angle Adjustable
- ✓ CCT Adjustable


Benefits

- ✓ High Energy Saving
- ✓ High Efficiency
- ✓ Eye Protection
- ✓ Long Life Time
- ✓ Private Mold

Application



Certificate



Body Colors



specifications

Item Number	Power (W)	Power Factor	Lumen (lm)	Efficiency (lm/W)	Input Current	CRI	Color Temperature	Life Time (hrs)
LPTRL-20FS01	20W	>0.67	1600-1760	80 ± 10	170mA	>83	WW/CW/NW/CCT	50000
LPTRL-30FS01	30W	>0.67	2400-2640	80 ± 10	270mA	>83	WW/CW/NW/CCT	50000
LPTRL-20FS02	20W	>0.67	1600-1760	80 ± 10	170mA	>83	WW/CW/NW/CCT	50000
LPTRL-30FS02	30W	>0.67	2400-2640	80 ± 10	270mA	>83	WW/CW/NW/CCT	50000



Technical specifications

On/Off Cycles	>100,000
Color Tolerance Adjustment (SDCM)	<6
IP	20
Class	II
LED Driver	DOB
LED Beads	COB 1919-14
Housing Color	White/Black
Pressure Resistant	3000V
Wire Diameter and Material	0.75 mm ² Copper Wire

Electrical Supply

Power Range	18-22W	27-33W
Frequency (Hz)	50/60	50/60
Voltage (V)	100-240	100-240
AC/DC	AC	AC
Input Current	170mA	270mA

Lights Material

Housing Material	Aluminium
Optical Material	Lens

Temperature

Operating Temperature	-15°C ~ 50°C
Testing Temperature	-20°C ~ 95°C

Packing Data

Item No	PCS/CTN	Gross Weight KG	Net Weight KG	Length CM	Width CM	Height CM
LPTRL-20FS01	20	6.6	3.8	41	32.9	23.5
LPTRL-30FS01	20	10	7.4	41.5	38.5	22.5

Product Size

Item No	Power	Length (mm)	Width (mm)	Height (mm)
LPTRL-20FS01	20W	93	65	207
LPTRL-30FS01	30W	94	75	207