

liper

2024.8



GERMANY LIPER ELECTRICAL CO.,LTD
ZHEJIANG LIPER LIGHTING TECHNOLOGY CO., LTD
Add:No. 580 Binhai 2nd Road, Yongxing Street, Longwan
District, Wenzhou City, Zhejiang Province, China
TEL:+86-577-8682 7777 86-577-8682 5888
FAX:+86-577-8681 5838
E-mail:admin@liperlighting.com

www.liperlighting.com
<https://www.facebook.com/LiperGermany>



Established in Germany in 1912...



LED



Das einzige unveränderliche Thema - Qualität

Brilliant light,
the unique eternal topic-----
quality.

liper

ESTABLISHED IN GERMANY IN 1912






Firmenprofil >>>

COMPANY PROFILE

Zhejiang Liper Beleuchtungstechnik AG (Kurze Einführung)



Im Dezember 2015 etablierten Liper Elektrogeräte GmbH in Deutschland und Zhejiang Liper Beleuchtungstechnik AG offiziell eine strategische Partnerschaft. Deutsche Führungskräfte und chinesische Vertreter unterzeichneten eine strategische Kooperationsvereinbarung in Deutschland. Die beiden Seiten beginnen mit der vielseitigen Zusammenarbeit, was signalisiert, dass Liper Beleuchtungstechnik AG zu einer neuen Etappe gegangen ist. Ein Flugzeugträger in internationaler Beleuchtungsindustrie wird bald abfahren.....

Wir werden die Vorteile der deutschen Industrietechnologie und den kontinuierlich verbesserten germanischen Geist voll integrieren, um ausgezeichnete Leistungen und nachhaltige Entwicklung zu erzielen und die ganzheitlichen Beleuchtungslösungen mit Weltrang für die weltweite kommerzielle Beleuchtung, Innenbeleuchtung und Außenbeleuchtung zu bieten. Dies ist eine Erweiterung des beidseitigen strategischen Layout. Darüber hinaus werden das neue Zusammenarbeitsmodell und die Strategie tiefgreifende Auswirkungen auf LED-Beleuchtungsindustrie haben.

Nach jahrelangen Entwicklungen hat Liper Beleuchtungstechnik AG sich zu einem globalen Beleuchtungsgeschäft entwickelt, was Forschung und Entwicklung, Produktion sowie Vertrieb integriert und mehr als 2.000 bestehende Mitarbeiter hat. Das Unternehmen hält sich an das "menschenorientierte" Entwicklungskonzept und legt großen Wert auf die Errichtung des Talentteams, technologische Talente kraftvoll einzuführen und zu trainieren. Das Unternehmen führt die deutschen fortschrittlichen Technologien und Ausrüstungen umfassend ein und errichtet F&E-Zentrum und Laborator auf nationaler Ebene. Es hat ein professionelles Team zum Management vom Betrieb, dessen Produkte auf der ganzen Welt verkauft werden. Zudem gründet es Niederlassungen und Geschäftsstellen in Europa, Mittlerem Osten, Südamerika, Südostasien, Afrika und anderen Regionen.

Durch die Zusammenarbeit zwischen Liper Beleuchtungstechnik AG und Liper Elektrogeräte GmbH in Deutschland, werden die beide Seiten ihre jeweiligen professionellen Vorteile im Produktionsmanagement und technischen Bereich voll integrieren, die Zusammenarbeit in F & E und Produkt durchzuführen, während in Markt, Kanal und Vertrieb zusammenzuarbeiten. Die "Liper Beleuchtung" entwickelt sich zum globalen Beleuchtungsgeschäft und zur führenden Beleuchtungsmarke Chinas. Bei der Gestaltung der internationalen Marke engagiert das Liper-Personal sich immer für die Gesinnung eines grünen, harmonischen, energiesparenden und kohlenstoffarmen neuen Lebens, um eine bessere Beleuchtungsumgebung für die ganze Welt zu schaffen und das Leben jeden Tag zu beleuchten!

Liper lässt die Welt energiesparender!

Zhejiang Liper Lighting Technology Co., Ltd


By officially reaching a strategic partnership on December 2015 upon signing of a strategic cooperation agreement between top leaders of the German company and representatives of its Chinese counterpart in Germany, Germany Liper Electric Co., Ltd and Zhejiang Liper Lighting Technology Co., Ltd have conducted all-round cooperation, marking a new stage of Liper's development. An aircraft carrier in the international lighting industry is about to set sail.....

We will fully integrate the German superior industrial technologies and improve German spirits to achieve excellence in performance and sustainable development, so as to provide world first-class integrated lighting solutions for the global commercial lighting, indoor lighting and outdoor lighting. It is not only an extension of the strategic layout of the two sides, but the new cooperation pattern and strategy will bring a far-reaching impact on the LED lighting industry.

After years of development, Liper now has grown into a global lighting enterprise engaged in product R & D, production and sales. The company currently employs more than 2000 people and attaches great importance to the establishment of high-quality talent team with great efforts made to introduce and cultivate talents of science and technology, under the "people-oriented" development philosophy. By widely introducing a full set of advanced technologies and equipment from Germany, setting up a state-level R & D center and laboratory, and putting business under management of the professional team, the company has exported its products to markets throughout the world with subsidiaries and offices in Europe, the Middle East, South America, Southeast Asia, Africa and other regions.

Based on business cooperation, Liper and Germany Liper will fully integrate their professional advantages in production management and technology for cooperation in R & D and products as well as in the fields of marketing, channels and sales, so that Liper will grow into a global lighting company as the leader brand in Chinese lighting industry. In shaping an international brand, Liper workers are still committed to promoting new views of green, harmonious, energy saving and low-carbon life, to create a better light environment for the world and light the life every day!

Liper make the world more energy saving!





Gruppenfoto von Vorstandsvorsitzender Herr Wang Renle und Staatspräsident
Board Chairman Mr.Wang Renle take group photo with Chinese former and current president



Links vierte in der zweiten Reihe
The second row of the fourth on the left



Rechts erst in der zweiten Reihe
The second row of the first on the right

Contents



LED FLOOD LIGHT

001-014



LED STREET LIGHT

015-028



LED SOLAR LIGHT

029-034



LED UFO LIGHT

035-038



LED LAMP

039-042



LED STEP LIGHT

043-044



LED WALL LIGHT

045-046



LED DOWN LIGHT

047-090



LED TRACK LIGHT

091-094



LED LOUVER FITTING

095-096



LED TUBE

097-102



LED STRIP LIGHT

103-104



LED MAGNETIC TRACK LIGHT

105-109



Brilliant light,
the unique eternal topic-----
quality.



LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-20BT01	20W	2000-2080LM	N	114x90x29mm
LPFL-30BT01	30W	3000-3080LM	N	136X118X29mm
LPFL-50BT01	50W	5000-5080LM	N	175X152X29mm
LPFL-100BT01	100W	10000-10500LM	N	236x202x32mm
LPFL-200BT01	200W	20000-20500LM	N	301X251X35mm
LPFL-300BT01	300W	30000-30500LM	N	330x302x35mm

LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h

IP66



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-20BT02	20W	2000-2080LM	N	114x90x29mm
LPFL-30BT02	30W	3000-3080LM	N	136X118X29mm
LPFL-50BT02	50W	5000-5080LM	N	175X152X29mm
LPFL-100BT02	100W	10000-10500LM	N	236x202x32mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-200BT02	200W	20000-20500LM	N	301X251X35mm
LPFL-300BT02	300W	30000-30500LM	N	330x302x35mm
LPFL-400BT02	400W	40000-40500LM	N	485x385x66mm
LPFL-500BT02	500W	50000-50500LM	N	485x385x66mm

Material

High Quality Aviation
Aluminum

Color Temperature





BS SERIES
LED FLOOD LIGHT

LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h

IP66



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-10BS01	10W	1000-1080LM	N	117X31X107mm
LPFL-20BS01	20W	2000-2080LM	N	117X31X107mm
LPFL-30BS01	30W	3000-3080LM	N	156X144X33mm
LPFL-50BS01	50W	5000-5080LM	N	199X36X160mm
LPFL-70BS01	70W	7000-5080LM	N	255X50X240mm
LPFL-100BS01	100W	10000-10500LM	N	331X50X280mm
LPFL-150BS01	150W	15000-15500LM	N	331X62X280mm
LPFL-200BS01	200W	20000-20500LM	N	331X88X280mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-10BS01-G	10W	1000-1080LM	N	167X55X107mm
LPFL-20BS01-G	20W	2000-2080LM	N	167X55X107mm
LPFL-30BS01-G	30W	3000-3080LM	N	202X56X156mm
LPFL-50BS01-G	50W	5000-5080LM	N	225X60X198mm



XT SERIES
LED FLOOD LIGHT

LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h

IP66



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-10XT01	10W	1000-1080LM	N	105X30X100mm
LPFL-20XT01	20W	2000-2080LM	N	124X30X114mm
LPFL-30XT01	30W	3000-3080LM	N	154X32X138mm
LPFL-50XT01	50W	5000-5080LM	N	205X32X175mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-100XT01	100W	10000-10500LM	N	280X34X258mm
LPFL-150XT01	150W	15000-15500LM	N	320X38X280mm

Material

High Quality Aviation
Aluminum

Color Temperature





LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h

IP66



Terminal Box


Color Temperature

RGB



Remote Control

RGB




Wireless Remote Control



IP66



200W



Material

High Quality Aviation Aluminum

Color Temperature

Warm White



Cool White



Natural White



LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-10X01	● 10W	890-950LM	N	137X32X118mm
LPFL-20X01	● 20W	1720-1810LM	N	180X37X187mm
LPFL-30X01	● 30W	2650-2730LM	N	193X37X197mm
LPFL-50X01	● 50W	4120-4200LM	N	258X42X257mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-100X01	● 100W	9150-9350LM	N	261X59X268mm
LPFL-150X01	● 150W	14100-14380LM	N	285X65X285mm
LPFL-200X01	● 200W	18800-19200LM	N	345X70X370mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-200X01	● 200W	20000-21000LM	N	345X110X375mm
LPFL-400X01	● 400W	40000-41000LM	N	405X105X430mm

 M SERIES
LED FLOOD LIGHT



LED
FLOOD LIGHT



M SERIES
LED FLOOD LIGHT




LED FLOOD LIGHT
Long Lifetime High Lumen Efficiency High CRI
Good Heat Dissipation No Radiation Energy Saving **IP66**
50W/100W/150W/200W/250W/400W/500W/600W

LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-50M01	50W	4980-5120LM	N	295X70X138mm
LPFL-100M01	100W	10560-11380LM	N	295X70X268mm
LPFL-150M01	150W	14800-15500LM	N	298X73X378mm
LPFL-200M01	200W	20800-21500LM	N	298X73X490mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-300M01	300W	28900-29600LM	N	573X73X378mm
LPFL-400M01	400W	39500-40200LM	N	573X73X490mm
LPFL-500M01	500W	48600-49700LM	N	573X73X600mm
LPFL-600M01	600W	58800-59500LM	N	573X73X710mm



Material
High Quality Aviation Aluminum

Color Temperature
Warm White
Cool White
Natural White





LED FLOOD LIGHT FOLDABLE/STRETCHABLE

(I. It can consistently use for 8 hours. II. It can consistently use for 4 hours. ★ III: SOS)



Easy to Carry



Car Charger



Normal Charger



Camping



Barbecue



Car Repairing

LED FLOOD LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Verdunklung DIM	Produktgröße Product Size
LPWK-100HW01	● 100W	3.7V/4400mAh	N	242x208x49mm
LPWK-200HW01	● 200W	3.7V/8800mAh	N	280x244x55mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPFL-30K01	● 30W	2400-3000LM	N	250X36X324mm
LPFL-30K02	● 30W	2400-3000LM	N	250X36X324mm
LPFL-30K03	● 30W	2400-3000LM	N	250X36X324mm
LPFL-30K04	● 30W	2400-3000LM	N	250X36X324mm
LPFL-30K05	● 30W	2400-3000LM	N	250X36X324mm



LED STREET LIGHT



AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Rohrdurchmesser einbauen Installation Pipe Diameter
LPSTL-50G01	50W	5130-6270LM	N	395x108x47mm	Ø 50/60mm
LPSTL-100G01	100W	10260-12540LM	N	458x120x49mm	Ø 50/60mm
LPSTL-150G01	150W	15390-18810LM	N	563x159x62mm	Ø 50/60mm
LPSTL-200G01	200W	20520-25080LM	N	650x173x62mm	Ø 50/60mm

Material

High Quality Aviation
Aluminum



Color Temperature

Warm White



Cool White



Natural White






LED STREET LIGHT

AC:100/220-240V CRI≥80 H:30000h

IP66



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Rohrdurchmesser einbauen Installation Pipe Diameter
LPSTL-20C01	20W	1900-2200LM	N	282X55X144mm	Ø 50mm
LPSTL-30C01	30W	2850-3300LM	N	282X55X144mm	Ø 50mm
LPSTL-50C01	50W	4750-5500LM	N	383X67X190mm	Ø 50mm
LPSTL-100C01	100W	9500-11000LM	N	490X85X225mm	Ø 50/60mm
LPSTL-100C01-G	100W	9500-11000LM	N	490X158X225mm	Ø 50/60mm
LPSTL-150C01	150W	14250-16500LM	N	600X95X272mm	Ø 50/60mm
LPSTL-200C01	200W	19000-22000LM	N	643X120X293mm	Ø 50/60mm



Material

High Quality Aviation
Aluminum

Color Temperature

Warm White




Cool White




Natural White






THE WIDTH OF THE ROAD 6-8M




A

THE WIDTH OF THE ROAD 6-8M




B

THE WIDTH OF THE ROAD 6-8M



C

THE WIDTH OF THE ROAD 6-8M



D

RECOMMENDED SPACING OF STREET LIGHTS					ROAD REFERENCE DATASHEET				
	A	B	C	D	Lm(cd/m²)	Uo	U1	TI[%]	EIR
50W	18-21m	18-21m	30-36m	32-38m	≥0. 75	≥0. 40	≥0. 60	≤15	≥0. 30
100W	30-36m	30-36m	52-68m	57-63m					
150W	42-48m	42-48m	57-63m	57-63m					
200W	45-51m	45-51m	57-63m	57-63m					



LED STREET LIGHT

AC:100/220-240V CRI≥80 H:30000h

IP66



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Rohrdurchmesser einbauen Installation Pipe Diameter
LPSTL-50A01	● 50W	3800-4360LM	N	373X80X300mm	Ø 50/60mm
LPSTL-100A01	● 100W	9200-9560LM	N	565X80X300mm	Ø 50/60mm
LPSTL-150A01	● 150W	12600-13350LM	N	757X80X300mm	Ø 50/60mm
LPSTL-200A01	● 200W	17500-18200LM	N	950X80X300mm	Ø 50/60mm





Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Produktgröße Product Size	Batterietyp Battery Type
LPSTL-400D01-Y	● 400W	80Ah	1050×390×88	LFP Battery



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Produktgröße Product Size	Batterietyp Battery Type
LPSTL-200E01-Y	● 200W	6000mAh	360x181x48	LFP Battery



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Produktgröße Product Size	Batterietyp Battery Type
LPSTL-100ES01-SS	● 100W	5AH	310x207x47	LFP battery
LPSTL-200ES01-SS	● 200W	6AH	385x207x47	LFP battery
LPSTL-300ES01-SS	● 300W	10AH	460x220x47	LFP battery
LPSTL-400ES01-SS	● 400W	15AH	580x236x47	LFP battery
LPSTL-500ES01-SS	● 500W	24AH	658x236x47	LFP battery




LED SOLAR LIGHT

CRI $\geq$ 80 H:20000h

IP65



Modell Model	Leistung Power	Opladtid Charging Time	Batteriekapazität Battery Capacity	Produktgröße Product Size	Rohrdurchmesser einbauen Installation Pipe Diameter	Batterietyp Battery Type
LPSTL-100D01	100W	4-6 Hours	15Ah	510X50X320mm	Ø 55-60mm	LFP Battery
LPSTL-200D01	200W	4-6 Hours	26Ah	510X50X320mm	Ø 55-60mm	LFP Battery





100W/200W
SOLAR STREET LIGHT IP65

LED SOLAR LIGHT

CRI≥80 H:20000h



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Produktgröße Product Size	Rohrdurchmesser einbauen Installation Pipe Diameter	Batterietyp Battery Type
LPSTL-100BS01-SS	100W	20Ah	670X350X590mm	Ø 50/60mm	LFP Battery
LPSTL-200BS01-SS	200W	30Ah	770X350X670mm	Ø 50/60mm	LFP Battery





LED SOLAR LIGHT


CRI≥80 H:20000h

Control Mode:lighting controlled intelligent controller

IP65



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Produktgröße Product Size	Rohrdurchmesser einbauen Installation Pipe Diameter	Batterietyp Battery Type
LPSTL-30BS01-SS	● 30W	6.5Ah	200X120X430mm	Ø 55mm	LFP Battery
LPSTL-60BS01-SS	● 60W	12Ah	450X125X450mm	Ø 55mm	LFP Battery
LPSTL-90BS01-SS	● 90W	16.5Ah	510X125X510mm	Ø 55mm	LFP Battery



LED WALL LIGHT

CRI≥80 H:20000h

Infrared Sensor




01:black 02:white

Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Produktgröße Product Size
LPWL-20B01	● 20W	3.6Ah	164X118X40mm
LPWL-40B01	● 40W	5.4Ah	224X118X48mm
LPWL-20B02	● 20W	3.6Ah	164X118X40mm
LPWL-40B02	● 40W	5.4Ah	224X118X48mm



HF SERIES
LED SOLAR LIGHT



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPFL-100HF01-SS	100W	6Ah	LFP Battery
LPFL-200HF01-SS	200W	12Ah	LFP Battery
LPFL-300HF01-SS	300W	18Ah	LFP Battery
LPFL-400HF01-SS	400W	24Ah	LFP Battery



HW SERIES
LED SOLAR LIGHT

LED SOLAR LIGHT

CRI≥80 H:20000h



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPFL-100HW01-SS	100W	5AH	LFP battery
LPFL-200HW01-SS	200W	10AH	LFP battery
LPFL-300HW01-SS	300W	15AH	LFP battery
LPFL-400HW01-SS	400W	20AH	LFP battery



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPFL-100HW02-SS	100W	5AH	LFP battery
LPFL-200HW02-SS	200W	10AH	LFP battery
LPFL-300HW02-SS	300W	15AH	LFP battery
LPFL-400HW02-SS	400W	20AH	LFP battery



HW SERIES

LED SOLAR LIGHT

LED SOLAR LIGHT

CRI≥80 H:20000h



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPFL-100HW03-SS	● 100W	5AH	LFP battery
LPFL-200HW03-SS	● 200W	10AH	LFP battery
LPFL-300HW03-SS	● 300W	15AH	LFP battery
LPFL-400HW03-SS	● 400W	20AH	LFP battery

MT SERIES

LED SOLAR LIGHT



YS : white YSB: black

Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPDL-30MT01-YS	● 30W	3.2V 5.4Ah	LFP Battery
LPDL-30MT01-YSB	● 30W	3.2V 5.4Ah	LFP Battery



C SERIES

LED SOLAR LIGHT

LED SOLAR LIGHT

CRI≥80 H:20000h



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPWL-100C01	● 100W	3.2V 2.2Ah	LFP Battery
LPWL-200C01	● 200W	3.2V 4.4Ah	LFP Battery

Infrared Sensor



Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LPFL-100C01-G	● 100W	3.7V 2.2Ah	LFP Battery
LPFL-200C01-G	● 200W	3.7V 2.2Ah	LFP Battery



MS SERIES
LED WORK LIGHT



Mobile Charge



Multi-functional
solar system

30W/40W



20h 15h 9h 6h



LED SOLAR LIGHT

CRI≥80 H:20000h



01:black 02:white


Modell Model	Leistung Power	Batteriekapazität Battery Capacity	Batterietyp Battery Type
LP-MS30A01	30W	6Ah	LFP Battery
LP-MS40A01	40W	12Ah	LFP Battery
LP-MS30A02	30W	6Ah	LFP Battery
LP-MS40A02	40W	12Ah	LFP Battery





FRESH LIGHT FOR SUPERMARKET

Ra>90(AVERAGE OF R1-R8)
R9>0(OBJECT MORE COLORFUL)



BS SERIES
LED UFO LIGHT





NEW

150W / 200W / 300W

IP65




+



=





150W/200W/300W

LED UFO LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPUF-150BS01	150W	16500-20250LM	N	Ø 385X120mm
LPUF-200BS01	200W	22000-20250LM	N	Ø 385X120mm
LPUF-300BS01	300W	33000-40500LM	N	Ø 385X120mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPUF-150BS01-Z	150W	16500-20250LM	N	Ø 480X250mm
LPUF-200BS01-Z	200W	22000-20250LM	N	Ø 480X250mm
LPUF-300BS01-Z	300W	33000-40500LM	N	Ø 480X250mm

Material

High Quality Aviation
Aluminum

Color Temperature







AS SERIES
LED LAMP




LED LAMP AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lampensockel Base
LPUF-20AS-02	20W	1750-1850LM	N	Ø 130X70mm	E27/B22
LPUF-40AS-02	40W	3750-3850LM	N	Ø 190X103mm	E27/B22
LPUF-60AS-02	60W	5750-5850LM	N	Ø 255X130mm	E27/B22



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lampensockel Base
LPUF-20AS-01	20W	1750-1850LM	N	Ø 130X70mm	E27/B22
LPUF-40AS-01	40W	3750-3850LM	N	Ø 190X103mm	E27/B22
LPUF-60AS-01	60W	5750-5850LM	N	Ø 255X130mm	E27/B22



D/ES SERIES
LED LAMP

LED LAMP AC:100/220-240V CRI≥80 H:20000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lampensockel Base
LPQP5DLED-01	5W	430-470LM	N	Ø 60X106mm	E27/B22
LPQP7DLED-01	7W	600-660LM	N	Ø 60X106mm	E27/B22
LPQP9DLED-01	9W	770-860LM	N	Ø 60X108mm	E27/B22
LPQP12DLED-01	12W	1005-1105LM	N	Ø 60X110mm	E27/B22
LPQP15DLED-01	15W	1235-1365LM	N	Ø 70X124mm	E27/B22
LPQP18DLED-01	18W	1520-1680LM	N	Ø 80X145mm	E27/B22
LPQP20DLED-01	20W	1710-1890LM	N	Ø 80X145mm	E27/B22



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lampensockel Base
LPQP20ES-01	20W	1900-2100LM	N	Ø 80X150mm	E27/B22
LPQP30ES-01	30W	2850-3150LM	N	Ø 100X185mm	E27/B22
LPQP40ES-01	40W	3610-3990LM	N	Ø 120X210mm	E27/B22
LPQP50ES-01	50W	4275-4725LM	N	Ø 138X240mm	E27/B22



A SERIES
LED STEP LIGHT

LED STEP LIGHT AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	IP IP	Produktgröße Product Size
LPWL-07A01-Y	7W	595-640LM	65	Ø 228x81x30mm
LPWL-07A01YCCT	7W	595-640LM	65	Ø 228x81x30mm



Color Temperature

Warm White

Cool White


Natural White

CCT Adjustable



A SERIES
LED STEP LIGHT

LED STEP LIGHT AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	IP IP	Produktgröße Product Size
LPWL-05A01-Y	5W	425-510LM	65	Ø 228x85x30mm
LPWL-05A01YCCT	5W	425-510LM	65	Ø 228x85x30mm



Color Temperature

Warm White

Cool White


Natural White

CCT Adjustable

C SERIES
LED WALL LIGHT

LED WALL LIGHT


AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	DIM DIM	Produktgröße Product Size
LPWL-08C01-Y	8W	440-480LM	N	Ø 70X165mm
LPWL-12C01-Y	12W	660-720LM	N	Ø 90X275mm



Color Temperature



C SERIES
LED WALL LIGHT



LED WALL LIGHT



AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	DIM DIM	Produktgröße Product Size
LPWL-10C01-Y	10W	550-600LM	N	Ø 80X230mm

Color Temperature










MA SERIES
LED DOWNLIGHT



IP65 Anti-insect





IP65 DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL20MA01-Y	20W	1600-1700LM	N	Ø 182X48mm
LP-DL30MA01-Y	30W	2400-2500LM	N	Ø 235X52mm
LP-DL40MA01-Y	40W	3200-3300LM	N	Ø 292X55mm
LP-DL50MA01-Y	50W	5000-5100LM	N	Ø 380X55mm
LP-DL60MA01-Y	60W	5130-5670LM	N	Ø 495X53mm
LP-DL20MA01-YG(SENSOR)	20W	1600-1700LM	N	Ø 182X48mm
LP-DL30MA01-YG(SENSOR)	30W	2400-2500LM	N	Ø 235X52mm




Color Temperature





MA SERIES
LED DOWNLIGHT





IP65 DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL30MA01-F	30W	2400-2500LM	N	215X57X215mm
LP-DL40MA01-F	40W	3200-3300LM	N	265X55X265mm
LP-DL30MA01-FG(SENSOR)	30W	2400-2500LM	N	215X48X215mm
LP-DL40MA01-FG(SENSOR)	40W	3200-3300LM	N	265X55X265mm



Color Temperature

Warm White

Cool White

Natural White






IP65 Anti-insect



MT SERIES
LED DOWN LIGHT



20W / 30W **IP65**
Diamond Downlight



LED WATERPROOF DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h




T/Y: white TH/YH: black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL20MT01-T	20W	1800-1900LM	N	255X125X72mm
LP-DL20MT01-Y	20W	1800-1900LM	N	Ø 206X72mm
LP-DL30MT01-Y	30W	2700-2800LM	N	Ø 256X76mm
LP-DL20MT01-TH	20W	1800-1900LM	N	255X125X72mm
LP-DL20MT01-YH	20W	1800-1900LM	N	Ø 206X72mm
LP-DL30MT01-YH	30W	2700-2800LM	N	Ø 256X76mm



T/Y: white TH/YH: black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL20MT02-T	20W	1800-1900LM	N	255X125X72mm
LP-DL20MT02-Y	20W	1800-1900LM	N	Ø 206X72mm
LP-DL30MT02-Y	30W	2700-2800LM	N	Ø 256X76mm
LP-DL20MT02-TH	20W	1800-1900LM	N	255X125X72mm
LP-DL20MT02-YH	20W	1800-1900LM	N	Ø 206X72mm
LP-DL30MT02-YH	30W	2700-2800LM	N	Ø 256X76mm



Color Temperature





MT SERIES
LED DOWN LIGHT





WITH SENSOR

Advised installation height : 3-5m

Max detection distance : 10m

It will turn off after people leave induction zone for 90s


LED WATERPROOF DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h



F: white FH: black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL30MT02-F	● 30W	2755-3045LM	N	205X60X205mm
LP-DL40MT02-F	● 40W	3610-3990LM	N	260X60X260mm
LP-DL30MT02-FH	● 30W	2755-3045LM	N	205X60X205mm
LP-DL40MT02-FH	● 40W	3610-3990LM	N	260X60X260mm



Color Temperature





MF SERIES
LED DOWN LIGHT



LED DOWN LIGHT

AC:100/220-240V CRI $\geq$ 80 H:30000h



T : white TB : black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL20MF01-T	● 20W	1710-1890LM	N	224X56X138
LP-DL30MF01-Y	● 30W	2570-2840LM	N	255X55X255
LP-DL20MF01-TB	● 20W	1710-1890LM	N	224X56X138
LP-DL30MF01-YB	● 30W	2570-2840LM	N	255X55X255



Material

High Quality Aviation Aluminum

Color Temperature





 MS SERIES
LED DOWN LIGHT



 GERMANY LIPER

LED DOWN LIGHT AC:100/220-240V CRI≥80 H:30000h

IP65



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPDL-25MS01-Y	● 25W	2125-2250LM	N	Ø 215X65mm
LPDL-35MS01-Y	● 35W	2975-3150LM	N	Ø 282X77mm
LPDL-45MS01-Y	● 45W	3825-4050LM	N	Ø 330X86mm
LPDL-25MS01-YCCT	● 25W	2125-2250LM	N	Ø 215X65mm
LPDL-35MS01-YCCT	● 35W	2975-3150LM	N	Ø 282X77mm
LPDL-45MS01-YCCT	● 45W	3825-4050LM	N	Ø 330X86mm



Color Temperature





MF SERIES
LED WALL LIGHT


IP65





Radar Sensor
Lux: <25lux
Sensing Distance: 5-8meter
Time-Delay: 90s

LED WALL LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL20MF01-TB-C	20W	1800LM	N	225X138X62
LP-DL20MF01-TB-CG(SENSOR)	20W	1800LM	N	225X138X62
LP-DL24MF01-YB-C	24W	2160LM	N	255X65X255
LP-DL24MF01-YB-CG(SENSOR)	24W	2160LM	N	255X65X255



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPDL-15MF01-F-C	15W	1275-1315LM	N	198X160X46mm


Material

High Quality Aviation
Aluminum


Color Temperature



EYE PROTECTION1st GENERATION




INSTALLATION METHOD



LED DOWN LIGHT AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPDL-40MW01-Y	40W	3600LM	N	Ø400X20mm
LPDL-50MW01-Y	50W	4500LM	N	Ø500X20mm



ALL IN ONE
2700K 4000K 6500K




Color Temperature

Warm White Cool White Natural White CCT Adjustable



LED DOWN LIGHT

AC:100/220-240V CRI $\geq$ 80 H:30000h



Material

High Quality Aviation Aluminum

Color Temperature

Warm White




Cool White



Natural White




CCT Adjustable




85mm

10W




108mm

15W



160mm

20W



208mm

30W



G SERIES
LED DOWN LIGHT

LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h

COB



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL10G01-Y	10W	780-840LM	N	Ø 85X53mm	Ø 75-80mm
LP-DL15G01-Y	15W	1150-1250LM	N	Ø 108X55mm	Ø 95-100mm
LP-DL20G01-Y	20W	1550-1650LM	N	Ø 165X85mm	Ø 145-150mm
LP-DL30G01-Y	30W	2300-2400LM	N	Ø 215X104mm	Ø 190-200mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL10G01-YB	10W	780-840LM	N	Ø 85X53mm	Ø 75-80mm
LP-DL15G01-YB	15W	1150-1250LM	N	Ø 108X55mm	Ø 95-100mm
LP-DL20G01-YB	20W	1550-1650LM	N	Ø 165X85mm	Ø 145-150mm
LP-DL30G01-YB	30W	2300-2400LM	N	Ø 215X104mm	Ø 190-200mm



G SERIES
LED DOWN LIGHT

LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h

SMD



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL10G02-Y	10W	780-840LM	N	Ø 85X53mm	Ø 75-80mm
LP-DL15G02-Y	15W	1150-1250LM	N	Ø 108X55mm	Ø 95-100mm
LP-DL20G02-Y	20W	1550-1650LM	N	Ø 165X85mm	Ø 145-150mm
LP-DL30G02-Y	30W	2300-2400LM	N	Ø 215X104mm	Ø 190-200mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL10G02-YB	10W	780-840LM	N	Ø 85X53mm	Ø 75-80mm
LP-DL15G02-YB	15W	1150-1250LM	N	Ø 108X55mm	Ø 95-100mm
LP-DL20G02-YB	20W	1550-1650LM	N	Ø 165X85mm	Ø 145-150mm
LP-DL30G02-YB	30W	2300-2400LM	N	Ø 215X104mm	Ø 190-200mm



GS SERIES
LED DOWNLIGHT

LED DOWN LIGHT


AC:100/220-240V CRI≥80 H:30000h



Y:white YB:black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPDL-10GS01-Y	10W	850-935LM	N	Ø85X53mm	Ø75-80mm
LPDL-15GS01-Y	15W	1275-1360LM	N	Ø108X55mm	Ø95-100mm
LPDL-10GS01-YB	10W	850-935LM	N	Ø85X53mm	Ø75-80mm
LPDL-15GS01-YB	15W	1275-1360LM	N	Ø108X55mm	Ø95-100mm

Color Temperature




H SERIES
LED DOWN LIGHT


LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h

Pre-Embedded



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPCL-10H02-Y	10W	850-935LM	N	Ø98X88mm	Ø75-80mm
LPCL-10H02-YB	10W	850-935LM	N	Ø98X88mm	Ø75-80mm



Y:white YB:black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPCL-10H01-Y	10W	850-935LM	N	Ø88X80mm	Ø75-80mm
LPCL-10H01-YB	10W	850-935LM	N	Ø88X80mm	Ø75-80mm

Color Temperature





A SERIES
LED DOWNLIGHT

LEDDOWNLIGHT

AC:100/220-240V CRI≥80 H:30000h




Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPCL-10A01-Y	10W	850-935LM	N	Ø75X100mm
LPCL-15A01-Y	15W	1275-1360LM	N	Ø75X150mm
LPCL-20A01-Y	20W	1700-1785LM	N	Ø95X150mm
LPCL-30A01-Y	30W	2550-2635LM	N	Ø115X135mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPCL-10A01-YB	10W	850-935LM	N	Ø75X100mm
LPCL-15A01-YB	15W	1275-1360LM	N	Ø75X150mm
LPCL-20A01-YB	20W	1700-1785LM	N	Ø95X150mm
LPCL-30A01-YB	30W	2550-2635LM	N	Ø115X135mm

Color Temperature



A SERIES
LED DOWNLIGHT

LEDDOWNLIGHT

AC:100/220-240V CRI≥80 H:30000h



Y:white YB:black

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPCL-15A01-YR	15W	1275-1360LM	N	Ø85X88mm
LPCL-15A01-YRCCT	15W	1275-1360LM	N	Ø85X88mm
LPCL-15A01-YBR	15W	1275-1360LM	N	Ø85X88mm
LPCL-15A01-YBRCCT	15W	1275-1360LM	N	Ø85X88mm






EN SERIES
LED DOWNLIGHT



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL10EN01-Y	10W	1000-1050LM	N	Ø 90x30mm	Ø 50-85mm
LP-DL18EN01-Y	18W	1800-1950LM	N	Ø 115x30mm	Ø 60-105mm
LP-DL24EN01-Y	24W	2400-2550LM	N	Ø 160x30mm	Ø 75-150mm
LP-DL36EN01-Y	36W	3600-3750LM	N	Ø 215x31mm	Ø 90-200mm

Color Temperature



LED DOWN LIGHT

AC:100/220-240V CRI>80 H:300000h




Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-DL12EM01-Y	12W	880-1020LM	N	Ø 172x29mm
LP-DL18EM01-Y	18W	1450-1530LM	N	Ø 222x29mm
LP-DL24EM01-Y	24W	1920-2060LM	N	Ø 282x29mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPDL-06EMS01-Y	6W	378-462LM	N	Ø 110x39mm
LPDL-12EMS01-Y	12W	864-1056LM	N	Ø 172x39mm
LPDL-18EMS01-Y	18W	1296-1584LM	N	Ø 222x39mm
LPDL-24EMS01-Y	24W	1836-2244LM	N	Ø 280x39mm
LPDL-06EMS01-YB	6W	378-462LM	N	Ø 110x39mm
LPDL-12EMS01-YB	12W	864-1056LM	N	Ø 172x39mm
LPDL-18EMS01-YB	18W	1296-1584LM	N	Ø 222x39mm
LPDL-24EMS01-YB	24W	1836-2244LM	N	Ø 280x39mm

Color Temperature





High Quality Aviation
Aluminum

Warm White Cool White Natural White



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-COB20BX01	 20W	1750-1900LM	N	Ø 160x50mm	 Ø 130-150mm
LP-COB30BX01	 30W	2550-2650LM	N	Ø 196x60mm	 Ø 160-185mm
LP-COB40BX01	 40W	3450-3550LM	N	Ø 225x70mm	 Ø 180-215mm
LP-COB50BX01	 50W	4350-4450LM	N	Ø 225x95mm	 Ø 180-215mm




ES SERIES
LED DOWNLIGHT

LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPDL-05ES01	5W	380-460LM	N	Ø90X37mm	Ø 70-80mm
LPDL-10ES01	10W	820-930LM	N	Ø114X37mm	Ø 95-105mm



Material

High Quality Aviation
Aluminum

Color Temperature



EASY TO REPLACE



EASY TO REPLACE






EC SERIES
LED DOWNLIGHT

LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h





Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL03EC01-Y	3W	210-240LM	N	Ø 85x25mm	Ø 40-75mm
LP-DL06EC01-Y	6W	430-510LM	N	Ø 116x25mm	Ø 55-105mm
LP-DL12EC01-Y	12W	880-1020LM	N	Ø 166x25mm	Ø 55-155mm
LP-DL18EC01-Y	18W	1450-1530LM	N	Ø 219x25mm	Ø 55-210mm



Color Temperature



EW SERIES
LED DOWN LIGHT



Color Temperature

Warm White

Cool White

Natural White





LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL03EW03-Y1	3W	210-240LM	N	Ø 98x28mm	Ø 70-90mm
LP-DL05EW03-Y1	5W	360-420LM	N	Ø 98x28mm	Ø 70-90mm
LP-DL06EW03-Y1	6W	430-510LM	N	Ø 120x28mm	Ø 90-110mm
LP-DL08EW03-Y1	8W	560-650LM	N	Ø 120x28mm	Ø 90-110mm
LP-DL12EW03-Y1	12W	880-1020LM	N	Ø 185x28mm	Ø 155-175mm
LP-DL18EW03-Y1	18W	1450-1530LM	N	Ø 225x28mm	Ø 195-215mm
LP-DL26EW03-Y1	26W	2110-2210LM	N	Ø 225x28mm	Ø 195-215mm





Color Temperature



LED DOWN LIGHT AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPDL-05EWS01-Y	5W	425-500LM	N	Ø 88X28mm	Ø 65-80mm
LPDL-08EWS01-Y	8W	680-720LM	N	Ø 112X30mm	Ø 90-100mm
LPDL-12EWS01-Y	12W	1020-1060LM	N	Ø 175X33mm	Ø 145-150mm
LPDL-18EWS01-Y	18W	1530-1570LM	N	Ø 222X35mm	Ø 185-200mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPDL-05EWS01-YCCT	5W	425-500LM	N	Ø 88X28mm	Ø 65-80mm
LPDL-08EWS01-YCCT	8W	680-720LM	N	Ø 112X30mm	Ø 90-100mm
LPDL-12EWS01-YCCT	12W	1020-1060LM	N	Ø 175X33mm	Ø 145-150mm
LPDL-18EWS01-YCCT	18W	1530-1570LM	N	Ø 222X35mm	Ø 185-200mm



A SERIES
LED DOWN LIGHT

LED DOWN LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-DL07A01-YX	● 7W	550-650LM	N	Ø 98x47mm	Ø 75-85mm
LP-DL10A01-YX	● 10W	850-920LM	N	Ø 115x47mm	Ø 95-105mm
LP-DL15A01-YX	● 15W	1350-1450LM	N	Ø 140x51mm	Ø 120-130mm
LP-DL20A01-YX	● 20W	1850-1950LM	N	Ø 180x44mm	Ø 160-170mm
LP-DL30A01-YX	● 30W	2850-2950LM	N	Ø 228x44mm	Ø 205-215mm
LP-DL10A01-FX	● 10W	850-950LM	N	Ø 101x43mm	Ø 80-90mm
LP-DL15A01-FX	● 15W	1350-1450LM	N	Ø 119x43mm	Ø 100-110mm
LP-DL20A01-FX	● 20W	1850-1950LM	N	Ø 140x45mm	Ø 120-130mm

IP20



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPDL-07AS01-Y	● 7W	595-635LM	N	Ø 95x26mm	Ø 75-85mm
LPDL-12AS01-Y	● 12W	1020-1060LM	N	Ø 112x28mm	Ø 90-100mm
LPDL-20AS01-Y	● 20W	1700-1740LM	N	Ø 172x28mm	Ø 145-150mm
LPDL-30AS01-Y	● 30W	2550-2590LM	N	Ø 225x28mm	Ø 180-200mm

Material

High Quality Aviation
Aluminum

Color Temperature



Natural White

CCT Adjustable



AS SERIES
LED DOWN LIGHT



IP65



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LPDL-07AS01-YW	● 7W	595-635LM	N	Ø 95x26mm	Ø 75-85mm
LPDL-12AS01-YW	● 12W	1020-1060LM	N	Ø 112x28mm	Ø 90-100mm
LPDL-20AS01-YW	● 20W	1700-1740LM	N	Ø 172x28mm	Ø 145-150mm
LPDL-30AS01-YW	● 30W	2550-2590LM	N	Ø 225x28mm	Ø 180-200mm




 G SERIES
LED CEILING LIGHT



LED CEILING LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-CL05G01-Y	● 5W	440-480LM	N	Ø88X42mm	Ø75-80mm
LP-CL05G02-Y	● 5W	440-480LM	N	Ø88X42mm	Ø75-80mm
LP-CL05G01-YB	● 5W	440-480LM	N	Ø88X42mm	Ø75-80mm
LP-CL05G01-YG	● 5W	440-480LM	N	Ø88X42mm	Ø75-80mm
LP-CL05G01-YBG	● 5W	440-480LM	N	Ø88X42mm	Ø75-80mm
LP-CL07G01-Y	● 7W	570-630LM	N	Ø88X42mm	Ø75-80mm
LP-CL07G02-Y	● 7W	570-630LM	N	Ø88X42mm	Ø75-80mm
LP-CL07G01-YB	● 7W	570-630LM	N	Ø88X42mm	Ø75-80mm
LP-CL07G01-YG	● 7W	570-630LM	N	Ø88X42mm	Ø75-80mm
LP-CL07G01-YBG	● 7W	570-630LM	N	Ø88X42mm	Ø75-80mm
LP-CL10G01-Y	● 10W	800-900LM	N	Ø120X52mm	Ø95-100mm
LP-CL10G02-Y	● 10W	800-900LM	N	Ø120X52mm	Ø95-100mm
LP-CL10G01-YB	● 10W	800-900LM	N	Ø120X52mm	Ø95-100mm
LP-CL10G01-YG	● 10W	800-900LM	N	Ø120X52mm	Ø95-100mm
LP-CL10G01-YBG	● 10W	800-900LM	N	Ø120X52mm	Ø95-100mm






CCT Adjust by Driver




CCT Adjust by Switch

Color Temperature

Warm White Cool White Natural White CCT Adjustable




 F SERIES
LED CEILING LIGHT





ANTI-DAZZLE DESIGN

BUCKLE DESIGN, SCREW FREE INSTALLATION

LED CEILING LIGHT AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-COB12FS01	12W	950-1050LM	N	Ø108x65mm	Ø 90-100mm
LP-COB12FS01-W	12W	950-1050LM	N	Ø108x65mm	Ø 90-100mm
LP-COB12FS02	12W	950-1050LM	N	Ø108x65mm	Ø 90-100mm
LP-COB12FS02-W	12W	950-1050LM	N	Ø108x65mm	Ø 90-100mm



BUCKLE DESIGN
SCREW FREE INSTALLATION

Material

High Quality Aviation
Aluminum


Color Temperature



 F SERIES
LED CEILING LIGHT



LED CEILING LIGHT AC:100/220-240V CRI≥80 H:30000h



F01
black inner circle

F02
black inner circle



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
LP-COB03F01-F1	3W	260-310LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB03F02-F1	3W	260-310LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB05F01-F1	5W	350-360LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB05F02-F1	5W	350-360LM	N	Ø 90x35mm	Ø 68-80mm

LP-COB08F01-F1	8W	630-720LM	N	Ø 110x50mm	Ø 90-100mm
LP-COB08F02-F1	8W	630-720LM	N	Ø 110x50mm	Ø 90-100mm

LP-COB12F01-F1	12W	950-1050LM	N	Ø 136x65mm	Ø 120-130mm
LP-COB12F02-F1	12W	950-1050LM	N	Ø 136x65mm	Ø 120-130mm



F SERIES
LED CEILING LIGHT

LED CEILING LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
-----------------	-------------------	----------------	--------------------	------------------------------	---------------------

LP-COB03F01-S	3W	220-280LM	N	Ø 72x35mm	Ø 60mm
LP-COB03F02-S	3W	220-280LM	N	Ø 72x35mm	Ø 60mm

LP-COB03F01-Y1	3W	260-310LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB03F02-Y1	3W	260-310LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB05F01-Y1	5W	350-360LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB05F02-Y1	5W	350-360LM	N	Ø 90x35mm	Ø 68-80mm

LP-COB08F01-Y1	8W	630-720LM	N	Ø 110x50mm	Ø 90-100mm
LP-COB08F02-Y1	8W	630-720LM	N	Ø 110x50mm	Ø 90-100mm

LP-COB12F01-Y1	12W	950-1050LM	N	Ø 136x65mm	Ø 120-130mm
LP-COB12F02-Y1	12W	950-1050LM	N	Ø 136x65mm	Ø 120-130mm



LP-COB05F01-YT1	5W	310-360LM	N	Ø 90x35mm	Ø 68-80mm
LP-COB05F02-YT1	5W	310-360LM	N	Ø 90x35mm	Ø 68-80mm



10°/20°/30° Selectable



FS SERIES
LED CEILING LIGHT


LED CEILING LIGHT

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size	Lochgröße Cutout
-----------------	-------------------	----------------	--------------------	------------------------------	---------------------

LPCOB-04FS01-YB	4W	320-340LM	N	Ø 40X41	Ø 30-35mm
LPCOB-04FS01-YBR	4W	320-340LM	N	Ø 35X41	Ø 30mm
LPCOB-04FS01-Y	4W	320-340LM	N	Ø 40X41	Ø 30-35mm
LPCOB-04FS01-YR	4W	320-340LM	N	Ø 35X41	Ø 30mm





 F SERIES
LED TRACK LIGHT




LED TRACK LIGHT

AC:100/220-240V CRI≥90 H:30000h




01:black 02:white

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPTRL-20F01	20W	1950-2150LM	N	93X65X207mm
LPTRL-30F01	30W	3325-3675LM	N	94X75X207mm
LPTRL-20F02	20W	1950-2150LM	N	93X65X207mm
LPTRL-30F02	30W	3325-3675LM	N	94X75X207mm



20W




30W

Material

High Quality Aviation Aluminum

Color Temperature



ALL IN ONE




2700K 4000K 6500K

E SERIES
LED TRACK LIGHT

ADJUSTABLE BEAM ANGLE

15°
30°
45°
60°

R9>0
15W/30W



GERMANY LIPER


LED TRACK LIGHT

AC:100/220-240V CRI≥80 H:30000h



01:black 02:white

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPTRL-15E01	15W	920-1050LM	N	130X63X95mm
LPTRL-30E01	30W	1950-2080LM	N	160X94X130mm
LPTRL-15E02	15W	920-1050LM	N	130X63X95mm
LPTRL-30E02	30W	1950-2080LM	N	160X94X130mm



Material

High Quality Aviation
Aluminum

Color Temperature

Warm White




Cool White

Natural White







LED LOUVER FITTING

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-LF60A60 40W	● 40W	3680-3960LM	N	596X7X596mm
LP-LF60A60 50W	● 50W	4780-4950LM	N	596X7X596mm
LP-LF120A30	● 40W	3680-3960LM	N	1196X7X296mm
LP-LF120A60	● 80W	7350-7580LM	N	1196X7X596mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-LF60E60 40W	● 40W	3250-3370LM	N	596X40X596mm
LP-LF60E60 50W	● 50W	4380-4510LM	N	596X40X596mm



straight connection



"I" shape connector



Right angle connection








"L" shape connector

LED TUBE

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPTL08D04	8W	600-680LM	N	600X30X37mm
LPTL16D04	16W	1260-1350LM	N	1200X30X37mm
LPTL10D04-2	16W	1260-1350LM	N	600X37X63mm
LPTL20D04-2	32W	2550-2670LM	N	1200X37X63mm
LPTL30D04-2	62W	4960-5090LM	N	1500X37X63mm



Color Temperature







T8 SERIES
LED TUBE

LED TUBE

AC:100/220-240V CRI≥80 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPTL10DS04	8W	600-680LM	N	588X26X30mm
LPTL20DS04	16W	1260-1350LM	N	1198X26X30mm
LPTL10DS04-2	18W	1420-1530LM	N	588X36X56mm
LPTL20DS04-2	36W	2880-2950LM	N	1198X36X56mm
LPTL30DS04-2	45W	3750-3870LM	N	1498X36X56mm



Color Temperature








T5 SERIES LED TUBE








T8 SERIES LED TUBE

LED TUBE





AC:100/220-240V CRI≥80 H:30000h




Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPTL04D05	4W	360-410LM	N	300x23x35mm
LPTL08D05	8W	720-820LM	N	600x23x35mm
LPTL12D05	12W	1050-1200LM	N	900x23x35mm
LPTL16D05	16W	1400-1610LM	N	1200x23x35mm




4W/8W/12W/16W




Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPTL08E02	8W	680-780LM	N	Ø 26x600mm
LPTL16E02	16W	1350-1480LM	N	Ø 26x1200mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
CW.A 1X18W	1X18W	1350-1450LM	N	625X30X46mm
CW.A 1X36W	1X36W	2600-2700LM	N	1232X30X47mm
CW.B 2X18W	2X18W	2600-2700LM	N	625X30X46mm
CW.B 2X36W	2X36W	4830-5400LM	N	1232X30X47mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
SY6120-H(LED)	1X20W	1650-1750LM	N	600X70X95mm
SY6140-H(LED)	1X40W	3350-3450LM	N	1200X70X95mm
SY6160-H(LED)	1X60W	5550-5650LM	N	1500X70X95mm




Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
SY6118-H	1X18W	1350-1450LM	N	662X98X106mm
SY6136-H	1X36W	2600-2700LM	N	1265X98X106mm
SY6218-H	2X18W	2600-2700LM	N	662X106X150mm
SY6236-H	2X36W	5200-5300LM	N	1265X106X150mm

LED STRIPLIGHT

AC: 220-240V CRI≥80 H:30000h


IP65
AC 220-240V



Power Supply
Carry 50M

Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPSL-7A01	7W/M	700LM/M	N	8mm
LPSL-12A01	12W/M	1200LM/M	N	11mm

IP20
DC24V



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LPSTL-20A01	20W/M	2400LM/M	N	10mm
LPSTL-25A01	25W/M	3000LM/M	N	15mm
LPSTL-30A01	30W/M	3600LM/M	N	28mm/30mm
LPSTL-40A01	40W/M	4800LM/M	N	40mm



LED MAGNETIC LIGHT

DC48V CRI≥90 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-CX-20CB-FG-10	10W	850-935LM	N	304X22X45mm
LP-CX-20CB-FG-20	20W	1700-1785LM	N	604X22X45mm
LP-CX-20CB-FG-30	30W	2550-2635LM	N	904X22X45mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-CX-20CB-GS-6	6W	510-595LM	N	134X22X45mm
LP-CX-20CB-GS-12	12W	1020-1105LM	N	220X22X46mm
LP-CX-20CB-GS-18	18W	1530-1615LM	N	328X22X47mm
LP-CX-20CB-GS-24	24W	2040-2125LM	N	435X22X47mm

Color Temperature



LED MAGNETIC LIGHT

DC48V CRI≥90 H:30000h



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-CX-20CB-DG2-10	10W	850-935LM	N	46X162mm
LP-CX-20CB-DG2-20	20W	1700-1785LM	N	56X196mm
LP-CX-20-HS-12	12W	1020-1080LM	N	40X300mm



Modell Model	Leistung Power	Lumen Lumen	Verdunklung DIM	Produktgröße Product Size
LP-CX-20CB-GS-ZD-6	6W	510-595LM	N	134X22X85mm
LP-CX-20CB-GS-ZD-12	12W	1020-1105LM	N	220X22X85mm
LP-CX-20CB-GS-ZD-18	18W	1530-1615LM	N	328X22X85mm
LP-CX-20CB-GS-ZD-24	24W	2040-2125LM	N	435X22X85mm



4 installation methods

1/2/3meters

