



Features

- ✓ Solar Energy
- ✓ IP65 Waterproof
- ✓ Timing Control
- ✓ Remote Control
- ✓ Lasting 2-3 Rainy Days

Benefits


- ✓ High Energy Saving
- ✓ High Efficiency
- ✓ Eye Protection
- ✓ Long Life Time
- ✓ Private Mold

Working Mode

Timing Control (Automatic Power Reduction Mode)

1hour: 100% brightness
2-3hour: 80% brightness
4-5hour: 60% brightness
6-7hour: 40% brightness
then 25% until dawn

Application



Certificate



specifications

Item Number	Model Power	Maximum Power	Battery Capacity	Solar Panel Size mm	CRI	Color Temperature	Life Time (hrs)
LP-DL30MT01-YS	30W	6W	3.2V/5.4Ah	177*267	>83	3000K	30000
LP-DL30MT01-YS	30W	6W	3.2V/5.4Ah	177*267	>83	4000K	30000
LP-DL30MT01-YS	30W	6W	3.2V/5.4Ah	177*267	>83	6500K	30000

Technical Specifications

IP	65
Class	III
LED Beads	2835 3V/1500MA 0.5W
Housing Color	Black/White
Maximum Power	6W
Voltage at Max	6V
AC/DC	DC
Current max	1A
Battery	3.2V/5.4AH
Model	Timing Control
Rainy Days	Lasting 2-3
Continuous Discharge Time	>24H
Wire Length	5meters

Lights Material

Housing Material	Plastic
Solar Panel Materials	Polysilicon

Temperature

Operating Temperature	-45°C ~ 50 °C
Testing Temperature	-45°C ~ 95 °C

Item No	PCS/CTN	Gross Weight KG	Net Weight KG	Length CM	Width CM	Height CM
LP-DL30MT01-YS	8	10.7	8.9	43	41	31

Item No	Power	Diameter (mm)	Height (mm)
LP-DL30MT01-YS	30W	206	72

Remote Controller

- ✓ **Intelligent light control**
- ✓ **Timer switch**
- ✓ **Brightness adjustment**



5 Meters Wire

- ✓ **Can installed anywhere**
- ✓ **Precision waterproof wire, resistant to tension, bending and breakage**



Cautions



The solar panel cannot be installed under the lamp, otherwise it will not light up or keep flickering



Solar panels cannot be installed in a place without or with less sunshine or will cause slow charging